

Safety Trailer Generator setup/breakdown and Power On/Off

Last Update: 02/16/2017

GENERATOR SETUP

- 1 - Get ramps out and secure to control cabinet floor. Make sure pins in holes
- 2 - Unstrap generator
- 3 - Turn ON winch controller after removing from velcro
- 4 - Push OUT button and guide generator down ramp
- 5 - Detach winch cable
- 6 - Position generator as far away from trailer as possible
- 7 - Turn OFF winch controller and return to velcro holder

POWER ON

- 1 - Unplug Generator Battery Charger
 - 2 - Start Generator
 - 3 - Plug extension cord in {Twist to lock}
 - 4 - Push Power Button on APC Uninterruptible Power Supply {UPS}
- **Everything should power up**
- 5 - Plug in Generator Battery Charger

POWER OFF

- 1 - Turn off all lights and heated door
 - 2 - Push and hold STOVE OFF button until says "SHUTTING DOWN"
- **The above MUST be done first!**
- 3 - Push Power Button on APC/UPS
 - 4 - Arrow down to "YES"
 - 5 - Push Enter Key (it appears as line down with arrow pointing to left)
 - 6 - Arrow down to "NO DELAY"
 - 7 - Push Enter Key (it appears as line down with arrow pointing to left)
- **APC/UPS should go into shut down. If not something was missed!**
- 8 - Unplug Generator Battery Charger
 - 9 - Stop Generator
 - 10 - Unplug extension cord {Twist to unlock. Use plug NOT cord!}

GENERATOR BREAKDOWN

- 1 - Position generator at foot of ramps
- 2 - Attach winch cable
- 3 - Turn ON winch controller after removing from velcro holder
- 4 - Push IN button and guide generator up ramp

****Do NOT winch all the way in!! Wheels MUST touch stops!**

5 - Turn OFF winch controller and return to velcro holder

6 - Strap generator

7 - Remove ramps and re secure in “BEDROOM”